

Software Defined Radio Technologies

--Versatile Transceivers--

Agenda

- Historical Background
- R & D of SDR
- Basic Concept of SDR
- Technological Issues
- Applications and Market for SDR
- Standardization and Regulation

2012/06/15

Wireless Communications Engineering I

1

Historical Background

– Military Communication System :

- In 1970's Smart Antenna
- The End of "Cold War" Regime
- In 1990's Speak Easy, MBMM
- 2 – 2000MHz
- SE Phase II Programmable Processor
- Voice Bridge : AM to FM

2012/06/15

Wireless Communications Engineering I

2

– Commercial :


- In 1996/14/20121 AMPS Base Station
- Multi Mode Base Station to Mini Cell
 - AMPS, N-AMPS, TDMA, CDPD, GSM, CDMA
- Soft Wave, DSP-Based Receiver

2012/06/15

Wireless Communications Engineering I

3

Software Radio “Phase Space”



2012/06/15

Wireless Communications Engineering I

4

SDR Related Projects

- Glomo (Global Mobile) :Distributed Packet Wireless Network
- SORT : Software Radio Technology
- SLATS : Software Libraries for Advanced Terminal Solutions
- PROMULA : Programmable Multimode Radio for Multimedia Wireless Terminals
- [MMITS Forum](#) → [SDR Forum](#)

2012/06/15

Wireless Communications Engineering I

5

SDR Study Group in Japan

1996— 1999	ARIB Study Group Radio Surveillance
1999 — Present	IEICE SDR Study Group
2000 — Present	TELEC SDR Approval FCC Collaboration Electronic Labeling Tamper-resistant Module

2012/06/15

Wireless Communications Engineering I

6

SDR Prototypes in Japan

- | | |
|-------------------|--------------------------|
| • ARIB | SDR Receiver |
| • CRL | ITS |
| • NTT | SDR Base station |
| • Toshiba | DCR |
| • Toyo Com. | Intelligent Base station |
| • Hitachi/Kokusai | SDR Transceiver |
| • NEC, Anritsu | Radio wave Monitoring |

2012/06/15

Wireless Communications Engineering I

7

Basic Concept of SDR

- Analog Radio
- Digital Radio



- Software Defined Radio
- Cognitive Radio ?

2012/06/15

Wireless Communications Engineering I


8

- Perfect Programmable Radio
- Programmable Analog Circuit
- RF: Multi band IF: Digital Processing
BB: Multi mode
- Reconfiguration through Air Interface
- High-level Digital Architecture

2012/06/15

Wireless Communications Engineering I

9




2012/06/15

Wireless Communications Engineering I

10

Model of SDR Receivers





2012/06/15

Wireless Communications Engineering I

11

Cognitive radio

A radio that **senses** its operational **environment** and can dynamically and autonomously **adjust** its radio operating parameters



Adaptive use of
Time, Frequency and Space

H. Harada, "cognitive radio technology", MWE2005, pp235-240, Nov.2005.

Communications Engineering I

12

View Point from System request (1)

Major Issues

- High-speed, Multi media (Voice, Image, Data) Transmission
- High Utilization of Spectrum
- Overcome of Multi path • Fading Problem

2012/06/15

Wireless Communications Engineering I

13

Expected Versatile Radio TX/RX

- Free Access
- Frequency Band
- Channel Width
- Modulation Scheme
- Antenna Directivity

2012/06/15


Wireless Communications Engineering I

14

View Point from System request (2)

Current Status

- Many Standards (AMPS, GSM, PDC, IS-95, PCS, PHS, CDMA-one, IMT-2000)
- Shortening of TAT (Increase of R&D Cost and Bug Patch)



Desirable Terminal

- Multi mode
- Software Oriented

2012/06/15

Wireless Communications Engineering I

15

The Need

Quad-band GSM
GPRS
Wideband CDMA
EDGE
GPS
Bluetooth
802.11b ...

Cram down
the funnel
of functions



- Large number of independently developed radio boards, all squeezed into a small mobile device ...
- You see one antenna, there are actually 3 or 4 ...
- Next month there will be a new wireless application
- Where will this end??



2012/06/15

Wireless Communications Engineering I

16

View Point from Device/Circuit Technology

- Small Size → Direct Conversion Receivers
- One-Chip → One-Chip Receivers
- Digital → Digital Receivers
- Software → Software Defined Receivers

2012/06/15

Wireless Communications Engineering I

17

Necessary Major Technologies

- Radio System Technology → Smart Radio Architecture
- Antenna → Adaptive Antenna
- Circuit → Circuit Architecture related Device
- Semiconductor Device →
Optimization of Analog Circuit
- Digital Signal Processing →
Adaptive & Optimized Algorithm

2012/06/15

Wireless Communications Engineering I

18

Feature of SDR Receivers

- Adaptive Modulation
~ FSK, GMSK, QPSK, $\pi/4$ QPSK, 16QAM, etc
- Adaptive Data Rate
~ 32kbps, 42kbps, 64kbps, 270kbps, 384kbps, 2Mbps, etc
- Adaptive Access Scheme
~ TDMA, FDMA, CDMA, SDMA, TDD, FDD, etc




What is a benefit and killer application ?

- World Wide Terminal
~ USA, EU, Aus, Japan, Taiwan, China, India, etc

2012/06/15

Wireless Communications Engineering I

19



Single Hardware Receivers

2012/06/15

Wireless Communications Engineering I

20

Technical Issues in SDR

- Antenna + RF Circuit
- Sampling Technology
- Signal Processing

2012/06/15

Wireless Communications Engineering I

21

TDD or FDD


- Requirements for Duplexer, RF Filter are quite different for TDD or FDD
- Bandwidth variable Duplexer

2012/06/15

Wireless Communications Engineering I

22

Direct Conversion Transceivers



2012/06/15

Wireless Communications Engineering I

23

Antenna+RF Circuit


- Adaptation to Environment
- MIMO Technology
- DOA, Spatial Processing
- Broad Band, Multi Band Characteristics
- MEMS Switch

2012/06/15

Wireless Communications Engineering I

24

The Software Defined Radio




2012/06/15

Wireless Communications Engineering I

25

What's wrong with this concept?

- Mitola's SDR can receive every band and channel concurrently!
- May be important for military, not necessary for civilian uses



Modified SDR

- ① Good enough to receive one channel at a time, but from **any band**, with **any channel bandwidth**, and **any modulation**
- ② Tunes channel of interest to zero IF
- ③ Wideband receiver (no RF preselect)

Standard	Modulation Scheme	Channel BW (MHz)
GSM	GMSK	0.200
EDGE	8PSK	0.200
Bluetooth	GFSK	1
CDMA IS95	QPSK CDMA	1.25
WCDMA/CDMA2000	QPSK/16QAM CDMA	1.25-5
802.11a/g	OFDM	20
802.11n	OFDM	10-20-40

2012/06/15

Wireless Communications Engineering I

26

How to make the RF/analog flexible?

- Push as much to digital as possible
 - With ADCs that dissipate milliwatts!
- Model the RF/analog signal processing on digital receiver
- Let's design an A/D centric RX, and work upstream towards the antenna
- Budget 10mW for A/D—today this gets us:
 - 8b, 40 MHz Nyquist ADC, or
 - 14b, 10 MHz Delta-Sigma ADC with 200 kHz bandwidth
- Choose best ADC for channel bandwidth and blocker profile
- Develop RX for GSM (200 kHz) and 802.11g (20 MHz)

2012/06/15



Wireless Communications Engineering I

27


Ultimate challenge: Wideband LNA

- **Departs from conventional narrowband RF practices**

- CG provides input match
- CS to provide extra gain & single to differential
- Input matching forms a 3rd order maximally-flat ladder filter, embedding bondwire
- 3rd order maximally-flat LC ladder filter as wideband load
- Measured: 18-20dB gain and $S_{11} < -10\text{dB}$ over 800M-5GHz



Wideband Frequency Tuning



- Divide & mux only
- No SSB mixers—unacceptable spurious tones


- Covers all major bands
- 2 VCO, only one is active at a time
- 21-33 mA dissipation for different bands
- 3 VCOs can give continuous frequency coverage

2012/06/15

Wireless Communications Engineering I

29

Block Diagram of Q-MOD





2012/06/15

Wireless Communications Engineering I

30

Combination of PPF+Freq. Div.




2012/06/15

Wireless Communications Engineering I


31

Measured Results (W-CDMA)

RF Frequency
800MHz
EVM 4.0%rms




RF Frequency
1.95GHz
EVM 3.1%rms



2012/06/15

Wireless Communications Engineering I

32




Software Antenna

2012/06/15

Wireless Communications Engineering I

33


Multi-band Antenna



2012/06/15

Wireless Communications Engineering I

34



X: Input Y: Output W: Weight τ : Delay Time

Adaptive Tapped Delay Line Array Antenna

2012/06/15

Wireless Communications Engineering I

35




Sampling Technologies

- Sampling Scheme
- Image Rejection
- Channel Selection
- Dynamic Range and AGC
- Trend in ADC and High speed
- Optimum Sampling Scheme

2012/06/15

Wireless Communications Engineering I

36



2012/06/15

Wireless Communications Engineering I

37


Sampling Scheme

- RF/IF/BB -Sampling
- Harder for ADC , Harder for Analog Circuit
- Nyquist/Over/Under -Sampling
 - Nyquist :
 - Sharp Analog LPF
 - Over :
 - Short Sampling Interval
 - Quantum Noise Reduction
 - Under :
 - Anti-aliasing BPF

2012/06/15

Wireless Communications Engineering I

38



2012/06/15

Wireless Communications Engineering I

39

Sampling in Time Domain (Interval : T_s)




Copying of Spectrum in Frequency Domain (Interval : $F_s = 1/T_s$)

2012/06/15

Wireless Communications Engineering I

40

Direct Sampling



2012/06/15

Wireless Communications Engineering I

41

Poisson Summation & Sampling Theorem

$$\sum_{k=-\infty}^{\infty} \exp(j2\pi k/T)/T = \sum_{n=-\infty}^{\infty} \delta(t - Tn)$$

$$\sum_{n=-\infty}^{\infty} s(Tn)\delta(t - Tn) = s(t) \sum_{n=-\infty}^{\infty} \delta(t - Tn)$$

2012/06/15

Wireless Communications Engineering I

42

Where to sample the wideband input?

- As soon as the signal of interest is at zero IF ...
- Clock-driven discrete-time analog signal processing gives greatest flexibility
- With 5 GHz-wide input band, what should be the sampling frequency?
 - Only the channel at zero IF is of interest
 - Everything else is unwanted
 - But we'll need an anti-alias filter with 100:1 range in cutoff if we sample 200 kHz to 20 MHz wide channels—impractical


2012/06/15

Wireless Communications Engineering I

43

Bring Down the Sample Rate (in Analog)

- Initial sample rate may be very high, to protect the wanted channel
- A/D conversion at this rate wastes power, as wanted signal band is much lower
- Analog decimation filter? Yes ...




Lindfors, et al., 2003
Helsinki University

2012/06/15

Wireless Communications Engineering I


44

Lowpass Sampler w/ Internal Anti-Alias



Rectangular Window Integration

- Main-lobe passes wanted signal at DC
- Side-lobes roll off with 20 dB/decade
- Notches @ nf_s for anti-aliasing
- Wider stop-band with higher f_s




2012/06/15

Wireless Communications Engineering I

45

RF Circuit for Direct Conversion




6-port Circuit
(Mixer-free Network Analyzer in Millimeter Wave)

2012/06/15

Wireless Communications Engineering I

46



2012/06/15

Wireless Communications Engineering I

47

3 Amplitudes → 1 Complex value

- Cross point of 3 Circles
- A,B,C : known Complex number
- r, r', r'' : known Real number
- $Z = I + jQ$: unknown Complex number

$$|Z - A| = r$$

$$|Z - B| = r'$$


$$|Z - C| = r''$$

Channel Selection

- PLL Frequency Synthesizer
 - Analog Signal Processing
 - Not Suitable for SDR
- Digital Down Converter
 - Programmable
 - Limit of Device Processing Speed
- Software Processing
 - Big Freedom
 - Limit of DSP Processing Speed

Fast Realization of SDR Receivers

- Reduce Sampling Speed : **Under Sampling**
- Reduce Resolution : **Gain Switch**
- Reduce Sampling Accuracy : **Low-IF Scheme**



An example of development scenario of a software defined radio

Circuit and Signal Processing for Wireless Communication (1)

- Oscillation, Frequency Synthesizer, PLL
- Amplification (Low Noise, High Power, Broad Band)
- Distortion Suppression
- Filtering (Analog, Digital), Spectrum Shaping
- Frequency Conversion, Mixing
- ADC, DAC
- Modulation & Demodulation: Analog, Digital
- Synchronization/Timing/Carrier Recovery

2012/06/15

Wireless Communications Engineering I

52

Circuit and Signal Processing for Wireless Communication (2)

- Interference Canceller, Multi-User Detection
- Equalizing, TOA
- Diversity
- Beam Forming, Null Shaping
- AGC, AFC
- Error Control: ARQ, FEC
- Scramble, Encryption, Authentication
- Data Compression

2012/06/15

Wireless Communications Engineering I

53

Requirements for Signal Processing

- Hardware
 - Selection of Clock Signal
 - Power Saving
 - Accuracy
 - Processing Unit Configuration
- Software Function
 - Channel Filtering
 - AFC, AGC, Offset Control
 - Demodulation/Modulation
 - Software Download

2012/06/15

Wireless Communications Engineering I

54


Dynamic Range & AGC

- Assignment of DR
 - Enlargement of DR by AGC
- Array Antenna
 - N-element Array Antenna :
Enlargement of DR, $10 \log N$ (dB)

2012/06/15

Wireless Communications Engineering I

55




Enlargement of DR by AGC (IF Sampling)

2012/06/15

Wireless Communications Engineering I

56





2012/06/15

Wireless Communications Engineering I

57


DR Widening and High-Speeding of ADC

- Relation between No. of Bit, SFDR, SNR
- Anti-aliasing Filter
 -  Reduction of Noise Drivers
- Randomization of Quantum Noise
- Dithering Circuit
- LUT (Look Up Table)
 -  Widening of DR

2012/06/15

Wireless Communications Engineering I

58



Analog Input Frequency MHz

2012/06/15

Wireless Communications Engineering I

59

Signal Processing Technology

- Specific Function SDR
- Implementation of Application Program
- Forecast of Programmable Device Trend
- Download Software

2012/06/15

Wireless Communications Engineering I

60

Target of Signal Processing in SDR

- Free Space
(Equalization, Interference Suppression, Diversity Combining)
- RF Circuit
(Distortion Compensation, DC Offset Compensation, Orthogonality Compensation)
⇒ Digital Assist Technology

2012/06/15

Wireless Communications Engineering I

61

Programmable Device


- DSP (Digital Signal Processor)
 - RISC Type Architecture
- ASSP (Application Specific Standard Products)
 - FFT Processor
- ASIC (Application Specific IC)
 - User Design
- FPGA (Field Programmable Gate Array)
 - Reconfigurable
- PLD (Programmable Logic Device)
 - Different Internal Structure
- MP (Micro Processor)
 - General Purpose Processor

2012/06/15

Wireless Communications Engineering I

62


DSP Trend



2012/06/15

Wireless Communications Engineering I


63



2012/06/15

Wireless Communications Engineering I

64



2012/06/15

Wireless Communications Engineering I

65

Direct Sampling Mixer

- RF-Front-End
- Sampling + Filtering + Mixing
- Suitable for SDR

2012/06/15

Wireless Communications Engineering I

66

Paradigm shift by CMOS Technology

Deep-submicron CMOS process

Disadvantage

- Very limited voltage headroom
- Considerable switching noise

Advantage

- Rise and fall times on the order of picoseconds
- Precise control of capacitance ratio

Voltage-domain



Time-domain

2012/06/15

Wireless Communications Engineering I

67

Analog → Digital Replacement

- Phase comparator → TDC (Time to Digital Converter)
- VCO → DCO (Digitally Controlled Oscillator)
- PLL → ADPLL (All Digital Phase Locked Loop)
- AGC → DPA (Digitally Controlled RF Power Amplifier)
- Heterodyne → Direct sampling


2012/06/15

Wireless Communications Engineering I

68

RF Front-end for SDR

Software Defined Radio



	Amplitude	Time
Analog	Continuous	Continuous
Sample	Continuous	Discrete
Digital	Discrete	Discrete

Discrete time receiver


→ DSM (Direct Sampling Mixer)

2012/06/15

Wireless Communications Engineering I

69

TI Bluetooth Transceiver




2012/06/15

Wireless Communications Engineering I

70

Discrete-Time Receiver

R.B.Stazewski et al., "All-Digital TX Frequency Synthesizer and Discrete-Time Receiver for Bluetooth Radio in 130-nm CMOS," IEEE JOURNAL OF SOLID-STATE CIRCUITS, VOL. 39, NO. 12, DECEMBER 2004



Amplitude

Analog

Time

Analog

Analog

Digital

Digital


Digital

2012/06/15

Wireless Communications Engineering I

71

Frequency characteristic of 2seri-3para DSM




2012/06/15

Wireless Communications Engineering I

72

Series-Parallel connection of DSM



2012/06/15

Wireless Communications Engineering I

73

Software Download

- Insertion of Media
- Fixed Telephone Line + Modem
- Provision of CD-ROM, FD
- Internet
- Service-Center
- Wireless Interface

2012/06/15

Wireless Communications Engineering I

74


SDR Market

- Satellite Mobile Communication
- Mobile Communication
- In-building PCS
- Pocket Wireless

2012/06/15

Wireless Communications Engineering I

75




Multi Media Universal Terminal

2012/06/15

Wireless Communications Engineering I

76




Base Station Antenna

2012/06/15

Wireless Communications Engineering I


77



2012/06/15

Wireless Communications Engineering I

78



FWA System

2012/06/15

Wireless Communications Engineering I

79


Standardization

- MMITS Forum → SDR Forum
 - Modular Multifunctional Information Transfer System
- de facto Standard
- Software Defined Radio Workshop
- Standardization(Mobile,Base Station,Handheld) is under way
- Approval & Electronic Label

What is the SDR Forum?


- **World's largest Forum for:**
 - Software (Defined) Radio
 - Cognitive (Smart) Radio
 - Military, public safety, commercial/consumer, avionics, space, academic domains
 - Technical, regulatory and market views
- **Around 120+ international members**
 - Manufacturers
 - Service providers & networks
 - Government agencies & regulators
 - Users
- **Standards development organization (SDO)**
 - Develops voluntary standards, recommendations and reference implementations
- **Non-profit organization**

What are Special Interest Groups ?



- Cross-disciplinary groups of users, operators, manufacturers
- Single market domain (e.g. Public Safety, Avionics, Networks...)
- Spans technical, regulatory, business case and user aspect

SIG Interactions




What is a Software Defined Radio?

What is a Software Defined Radio (SDR)?

A radio is considered to be a software defined radio (SDR) if:

- Some or all of the baseband or RF signal processing is accomplished through the use of software
- The signal processing can be modified post manufacture

(Definition based on draft being developed jointly by the SDR Forum and IEEE P1900.1)



SDR: FCC Definition

A radio that includes a transmitter in which the operating parameters of frequency range, modulation type or maximum output power (either radiated or conducted), or the circumstances under which the transmitter operates in accordance with Commission rules, can be altered by making a change in software without making any changes to hardware components that affect the radio frequency emissions.

SDR: ITU Definition

- A radio in which RF operating parameters including but not limited to frequency range, modulation type, or output power can be set or altered by software, and/or the technique by which this is achieved.
- NOTE 1 – Excludes changes to operating parameters which occur during the normal pre-installed and predetermined operation of a radio according to a system specification or standard.
- NOTE 2 – SDR is an implementation technique applicable to many radio technologies and standards.
- NOTE 3 – Within the mobile service, SDR techniques are applicable to both transmitters and receivers.

What is a Cognitive Radio?


Cognitive Radio (Smart Radio)

- A radio or system that utilizes a cognitive control mechanism that can sense and autonomously reason about the surrounding radio environment and adapt to it accordingly.
- For example, a cognitive radio should be able to detect other radio transmissions and automatically select unused frequency bands in order to increase effectiveness in the usage of the spectrum.
- The term radio is used broadly to include cognitive radio systems.
- Cognitive radio systems could include components such as sensors and network management systems that are external to the radio but are accessible via a network.
- In such a system, individual radio sets might rely on these external elements for much of their cognitive capability.


(Definition is based on draft v0.17 document being developed jointly by the SDR Forum and IEEE P1900.1)

What is the Software Communications Architecture (SCA)?

Software Communications Architecture (SCA) (part of a US DoD procurement specification)



SCA Diagram: Secure Tactical Radio



Source: US Department of Defense, Joint Tactical Radio System

SDRF Networking Waveform Protocol Stack Reference Model

