

Noise and Interference

[Contents]

- Noise
- Interference
- Array Signal Processing for Interference Canceling
- RF Front-end Signal Processing
- Spatial Fading Emulator

2013/05/15

Wireless Communication Engineering I

1

• Noise and Interference in Wireless Communication Systems


Noise and Interference determine a quality of communication system and an achievable bit rate.

2013/05/15

Wireless Communication Engineering I

2


Schematic diagram of wireless communication systems



2013/05/15

Wireless Communication Engineering I


3



2013/05/15

Wireless Communication Engineering I

4



: receiver noise,
sensitivity suppression
: inter-modulation
: spurious reception

2013/05/15

Wireless Communication Engineering I

5

Noise and Interference in TX

- Transmitter noise
(Continuous spectrum noise below 60dB)
 - ← Spectrum Impurity (**Phase Noise**) in Local Oscillator
High S / N Oscillators are required.
- Spurious radiation (Line spectrum noise)
 - ← **Non-linearity** in power-amplifiers and/or frequency converter
Sharp Band pass Filters are required.
- Inter-modulation in TX
 - ← Strong another signal entering through TX antenna
High-Q Filters and Isolators are required.

2013/05/15

Wireless Communication Engineering I

6

Noise and Interference in Radio Wave Channel

- External noise
 - ← Lightning, Solar noise, Thermal noise, Artificial noise, ..., impulsive and continuous spectrum noise
- Co-channel interference
 - Sensitivity suppression
- Adjacent-channel interference
 - Side-lobe spectrum of adjacent channel signal

2013/05/15

Wireless Communication Engineering I

7

Noise and Interference in RX

- Receiver noise

Thermal white noise power = kTB

(k : Boltzmann constant = 1.38×10^{-23} [J/K])

T : Temperature B : Bandwidth)

@ $T = 300K \rightarrow -174$ [dBm/Hz]

Noise Figure : $(F = SN_{in} / SN_{out})$

Noise Measure : $(M = (F - 1) / (1 - 1/G))$

G : Gain

2013/05/15

Wireless Communication Engineering I

8

- Sensitivity suppression
Low gain before IF-stage, Sharp Band-pass Filter in RF-stage and IF-stage, and Low noise in LO are required.
- Spurious reception
Image frequency
- Inter-modulation in RX
3rd order and 5th order IMD are dominant.

2013/05/15

Wireless Communication Engineering I

9

Noise

- Thermal noise
The equivalent noise power spectrum density in W/Hz generated in any ideal coherent amplifier of electromagnetic wave

$$N_0 = hf / [e^{hf/kT} - 1] \cong kT$$

When frequency f is small enough ($< 10^{10}$ Hz)

$$N_0 \Rightarrow kT$$

where h : Planck constant $\approx 6.6252 \times 10^{-34} [J \cdot s]$

k : Boltzman constant

2013/05/15

Wireless Communication Engineering I

10

- Shot noise: Poisson Process
 $N_0 \propto I_0$ (DC current)
- Switching noise of Capacitance
 kT/C

2013/05/15

Wireless Communication Engineering I

11

Equivalent Noise Temperature of Noise Sources

$$T_{\text{equiv}} = T_1 + \frac{T_2}{G_1} + \frac{T_3}{G_1 G_2} + \dots$$

Since the noise temperature and noise figure F_e referenced to Temperature T_0 are related by


$$F_e = \frac{T_e}{T_0} + 1$$

2013/05/15

Wireless Communication Engineering I

12

Cascade Connection of LNA with Noise Figure F and Gain G



2013/05/15

Wireless Communication Engineering I

13

The corresponding overall noise figure is then given by the Friis noise formula,

$$F_{\text{total}} = F_1 + \frac{F_2 - 1}{G_1} + \frac{F_3 - 1}{G_1 G_2} + \dots$$

$$G_{\text{total}} = G_1 G_2 G_3 \dots$$

F_1 should be **minimum**.

2013/05/15

Wireless Communication Engineering I

14

2-Stage Case → Noise Measure

$$F_{12} = F_1 + \frac{F_2 - 1}{G_1} \quad F_{12} \geq F_{21}$$

$$F_{21} = F_2 + \frac{F_1 - 1}{G_2} \quad M_1 = \frac{F_1 - 1}{1 - \frac{1}{G_1}} \geq \frac{F_2 - 1}{1 - \frac{1}{G_2}} = M_2$$

2013/05/15

Wireless Communication Engineering I

15

Power-limited System & Interference-limited System

- **Propagation-limited systems**
Thermal and man-made noise play the most important roles in large-scale systems.
(i.e. **satellite systems**)
- **Interference-limited systems**
Unwanted interfering signals from nearby cells in which the same frequency is reused, play the most critical role in **cellar and micro cellar systems**.

2013/05/15

Wireless Communication Engineering I

16

- **Propagation delay**

Severe inter-symbol interference is possible if the differential delay between two signals is too great and the received power levels are nearly equal.

- **Simulcast transmitting frequency offsets**

In digital paging applications, frequencies are often offset from each other to mitigate the effects of standing wave interference patterns, which could otherwise cause localized areas of poor coverage. The offset frequency increments for digital messaging systems having symbol rates up to 3,200 symbols per second are 100-450Hz. The maximum offset of the carrier frequency is chosen to never exceed $\pm 600\text{Hz}$.

2013/05/15

Wireless Communication Engineering I

17

Interference in Mobile Communication Systems

- **Personal Radio**

(Simplex: Signal channel, non-simultaneous transmission)
Maximum Interference Effect

- **MCA**

(Dusimplex: Two channels, non-simultaneous transmission)
Medium Interference Effect

- **Automotive Telephone**

(Duplex: Two channels, simultaneous transmission)
Low Interference Effect

2013/05/15

Wireless Communication Engineering I

18

Interference Cancel by Array Signal Processing


Spatial Signal Processing

- SINR Criteria
- MSE Criteria

2013/05/15

Wireless Communication Engineering I

19



2013/05/15

Wireless Communication Engineering I

20

$\mathbf{x}(t) = \mathbf{a}_s s(t) + \mathbf{a}_i i(t) + \mathbf{n}(t)$: received signal model

$\mathbf{a}_s = \mathbf{a}(\theta_s)$: spatial signature for desired signal $s(t)$

θ_s : known

$\mathbf{a}_i = \mathbf{a}(\theta_i)$: spatial signature for undesired signal $i(t)$

θ_i : known

$\mathbf{n}(t)$: additive noise at the receiver

2013/05/15

Wireless Communication Engineering I

21

- Linear Signal Processing

$y(t) = \mathbf{w}^+ \mathbf{x}(t)$: output signal

\mathbf{w} : weight vector for linear processing


$$\begin{aligned} y(t) &= y_s(t) + y_i(t) + y_n(t) \\ &= \mathbf{w}^+ \mathbf{a}_s s(t) + \mathbf{w}^+ \mathbf{a}_i i(t) + \mathbf{w}^+ \mathbf{n}(t) \end{aligned}$$

$$\text{SINR} = \frac{E[|y_s(t)|^2]}{E[|y_i(t)|^2] + E[|y_n(t)|^2]}$$

2013/05/15

Wireless Communication Engineering I


22



2013/05/15

Wireless Communication Engineering I

23



2013/05/15

Wireless Communication Engineering I

24

$\mathbf{a}(\theta)$: array mode vector with DOA, θ

e.g. ULA (Uniform Linear Array)

$$\mathbf{a}(\theta) = (1, Z, Z^2, \dots)^t$$

$$Z = e^{i \frac{2\pi}{\lambda} \Delta \sin \theta}$$

Δ : inter element spacing

λ : wave length ($= c/f$)

2013/05/15

Wireless Communication Engineering I

25

- Interference Canceling principle →
ZF (Zero Forcing) Optimum Weight Vector

$$\mathbf{w} = c[\mathbf{e}_s - \theta \mathbf{e}_i]$$

$$\mathbf{w}^+ \mathbf{e}_i = \mathbf{e}_s^+ \cdot \mathbf{e}_i - \theta^* = \theta^* - \theta^* = 0$$

$$\therefore \mathbf{w} \perp \mathbf{e}_i$$

c : some constant

where

$$\mathbf{e}_s = \mathbf{a}_s / |\mathbf{a}_s|, \mathbf{e}_i = \mathbf{a}_i / |\mathbf{a}_i|$$

$$\theta = \mathbf{a}_i^+ \cdot \mathbf{a}_s / |\mathbf{a}_i| |\mathbf{a}_s| = \mathbf{e}_i^+ \mathbf{e}_s : \text{spatial correlation } (0 \leq |\theta| \leq 1)$$

2013/05/15

Wireless Communication Engineering I

26

$$\begin{aligned} y_s(t) &= \mathbf{w}^+ \cdot \mathbf{a}_s s(t) = (\mathbf{e}_s^+ - \theta^* \mathbf{e}_i^+) \mathbf{a}_s s(t) \\ &= |\mathbf{e}_s| (1 - |\theta|^2) \mathbf{a}_s s(t) \end{aligned}$$

$$S = E[|y_s(t)|^2] = |\mathbf{a}_s|^2 (1 - |\theta|^2)^2 E[|s(t)|^2]$$

$$y_i(t) = \mathbf{w}^+ \cdot \mathbf{a}_i i(t) = 0$$

$$I = E[|y_i(t)|^2] = 0$$

2013/05/15

Wireless Communication Engineering I

27

$$\begin{aligned} y_n(t) &= \mathbf{w}^+ \mathbf{n}(t) \\ &= (\mathbf{e}_s^+ - \theta^* \mathbf{e}_i^+) \cdot \mathbf{n}(t) \end{aligned}$$

$$\begin{aligned} N &= E[|y_n(t)|^2] = (\mathbf{e}_s^+ - \theta^* \mathbf{e}_i^+) E[\mathbf{n}(t) \mathbf{n}(t)^+] (\mathbf{e}_s - \theta \mathbf{e}_i) \\ &= (\mathbf{e}_s^+ - \theta^* \mathbf{e}_i^+) \sigma_n^2 I (\mathbf{e}_s - \theta \mathbf{e}_i) \\ &= \sigma_n^2 (1 - \theta^* \theta - \theta^* \theta + \theta^* \theta) \\ &= \sigma_n^2 (1 - |\theta|^2) \end{aligned}$$

2013/05/15

Wireless Communication Engineering I

28

SNR for ZF

$$\therefore \Gamma = S/(I + N) = \frac{P_s |\mathbf{a}_s|^2}{\sigma_n^2} [1 - |\theta|^2]$$

$$P_s = E[|s(t)|^2]: \text{average signal power}$$

$$\sigma_n^2 I = E[\mathbf{n}(t)\mathbf{n}(t)^+]: \text{average noise power}$$

2013/05/15

Wireless Communication Engineering I

29

- Maximizing SINR principle → DCMP (Directional Constraint Minimization of Power)

Directional Constraint $\mathbf{w}^+ \mathbf{a}_s = \text{constant}$

$$\mathbf{w} = c \left[\mathbf{e}_s - \frac{\theta}{1 + \frac{\sigma_n^2}{P_i |\mathbf{a}_i|^2}} \mathbf{e}_i \right]$$

2013/05/15

Wireless Communication Engineering I

30

$$\text{SINR: } \Gamma = \frac{P_s |\mathbf{a}_s|^2}{\sigma_n^2} \left[1 - \frac{|\theta|^2}{1 + \frac{\sigma_n^2}{P_i |\mathbf{a}_i|^2}} \right]$$

$$P_i = E[|i(t)|^2]: \text{average interference power}$$

2013/05/15

Wireless Communication Engineering I

31

When $\mathbf{a}_s \perp \mathbf{a}_i$ (spatially orthogonal)

$\mathbf{w}_{\text{ZF}}, \mathbf{w}_{\text{DCMP}} \rightarrow \mathbf{e}_s$ Beam Forming Principle,
MRC (Maximum Ratio Combining)

$$\Gamma \rightarrow \frac{P_s |\mathbf{a}_s|^2}{\sigma_n^2}: \text{SNR}$$

2013/05/15

Wireless Communication Engineering I

32


- Direction Finding Technique \Rightarrow Estimate of $SS, \mathbf{a}(\theta)$
- MUSIC (Multiple Signal Classification)
- ESPRIT
 - SUB-SPACE METHOD
 - A PRIORI KNOWLEDGE OF SIGNAL IS **NOT** REQUIRED

\rightarrow Blind Estimation

2013/05/15

Wireless Communication Engineering I

33



2013/05/15

Wireless Communication Engineering I

34

Super resolution techniques

- Model-based parameter estimation
- Fine resolution than **Sampling Theorem**
- MUSIC, ESPRIT : Powerful DOA techniques especially in **radar application**.


2013/05/15

Wireless Communication Engineering I

35

RF FRONT-END FOR SPATIAL PROCESSING

FREQUENCY CONVERSION FROM RF TO IF




2013/05/15

Wireless Communication Engineering I

37


ARRAY PROCESSING by Gilbert Cell and Transformer



2013/05/15

Wireless Communication Engineering I

38




2013/05/15


Wireless Communication Engineering I

39

DESIRED




UNDESIRABLE




2013/05/15

Wireless Communication Engineering I

40



MEASURED RESULTS BEFORE AND AFTER SIGNAL PROCESSING for Interference Canceling



Spatial Fading Emulator

- The field testing of radio transmission techniques is often **time-consuming**.
- The evaluation of cellular base station antenna arrays **in an anechoic chamber** is needed.
- With the use of an ESPAR antenna, the superposition of scattered waves can be made easily.

Agenda


- Background
- Spatial Fading Emulator
- Deterministic Estimation
- Complex Angle
- Experimental Results
- Conclusion & Future works

2013/05/15

Wireless Communication Engineering I

45

Propagation of mobile communication



Fading wave caused by the superposition of scattered waves


→ With the use of an ESPAR antenna, fading waves can be easily made.

2013/05/15

Wireless Communication Engineering I

46

Structure of Emulator



2013/05/15

Wireless Communication Engineering I

47

Control of bias voltages to varactors



Control of \mathbf{Y}_L



Control of $[i_1, i_2, \dots, i_r]$



Control of multiple waves

2013/05/15

Wireless Communication Engineering I

48

Approximated Equation of Received Signal

Received signal model ($\mathbf{a}(\theta_i)$: Array mode vector) θ_i : DOA

$$\mathbf{r}(t) = \sum_{i=1}^N \beta_i \mathbf{a}(\theta_i) \mathbf{s}(t) + \mathbf{n}(t) \quad \rightarrow \text{Number of estimate parameters is } 2 \times N (\beta_i, \theta_i)$$

[approximated by Taylor Series Expansion]

$$\mathbf{r}(t) \simeq \gamma \mathbf{a}(\tilde{\theta} + \xi) \mathbf{s}(t) + \mathbf{n}(t)$$

γ and θ , for the case where f is minimum, become the Maximum likelihood values.

$$\gamma = \sum \beta_i, \quad \xi = \sum \beta_i \Delta \theta_i / \gamma, \quad \theta_i = \tilde{\theta} + \Delta \theta_i$$

2013/05/15

Wireless Communication Engineering I

49

Approximated Equation of Received Signal

$$\begin{aligned} \sum_{i=1}^N \beta_i \mathbf{a}(\tilde{\theta} + \Delta \theta_i) &\simeq \sum_{i=1}^N \beta_i [\mathbf{a}(\tilde{\theta}) + \Delta \theta_i \frac{\partial \mathbf{a}(\tilde{\theta})}{\partial \theta}] \\ &= (\sum \beta_i) \mathbf{a}(\tilde{\theta}) + (\sum \beta_i \Delta \theta_i) \frac{\partial \mathbf{a}(\tilde{\theta})}{\partial \theta} \\ &= \gamma \mathbf{a}(\tilde{\theta}) + \eta \frac{\partial \mathbf{a}(\tilde{\theta})}{\partial \theta} \quad \gamma = \sum_{i=1}^N \beta_i \\ &= \gamma [\mathbf{a}(\tilde{\theta}) + \xi \frac{\partial \mathbf{a}(\tilde{\theta})}{\partial \theta}] \quad \eta = \sum_{i=1}^N \beta_i \Delta \theta_i \\ &\simeq \gamma [\mathbf{a}(\tilde{\theta} + \xi)] \quad \xi = \frac{\eta}{\gamma} \end{aligned} \quad (6)$$

$$\mathbf{r}(t) \simeq \gamma \mathbf{a}(\tilde{\theta} + \xi) \mathbf{s}(t) + \mathbf{n}(t) \quad [\text{approximate}]$$

$\theta + \xi$ is a complex angle, the angular spread is also expressed.

2013/05/15

Wireless Communication Engineering I

50

Parameter Estimation

$\mathbf{s}(t)=1$, because a Network Analyzer is used.

$$f \stackrel{\text{def}}{=} |r_1 - \gamma a_1|^2 + |r_2 - \gamma a_2|^2 + \dots + |r_M - \gamma a_M|^2$$

→ Estimate γ and θ where f is minimum ($\theta = \theta_1 + j\theta_2$)


1. Least mean square w.r.t. γ

$$\hat{\gamma} = \frac{\mathbf{a}^H \mathbf{r}}{|\mathbf{a}|^2}$$

2. The cost function is

$$\begin{aligned} f &= |\mathbf{r} - \hat{\gamma} \mathbf{a}(\theta)|^2 \\ &= |\mathbf{r}|^2 - \frac{|\mathbf{a}(\theta)^H \mathbf{r}|^2}{|\mathbf{a}(\theta)|^2} \end{aligned}$$

→ Minimum



2013/05/15

Wireless Communication Engineering I

51

Distribution of a Complex Angle

- Distribution of a Complex Angle is $\sum \beta_i \Delta \theta_i / \sum \beta_i$
→ the ratio of two Gaussian distributions

$$p(\xi) = \frac{1}{2C} \frac{1}{(\xi^2/C^2 + 1)^{3/2}} \quad [\text{M-distribution}]$$

$$C = \sqrt{\theta_i^2}$$

Parameter C is the absolute first order moment of M-distribution and equal to the standard deviation of DOA of the scattering wave are in agreement.

2013/05/15

Wireless Communication Engineering I

52

- Random FM noise

$\theta(t)$ fluctuates randomly \rightarrow FM noise

A pdf of $\dot{\theta}$, $p(\dot{\theta})$ is

$$p(\dot{\theta}) = \frac{1}{2} \sqrt{\frac{b_0}{b_2}} \left[1 + \frac{b_0}{b_2} \dot{\theta}^2 \right]^{-3/2}$$

2013/05/15

Wireless Communication Engineering I

53

Error of parameter estimation

- Additive noise including system error is

$$|\mathbf{n}|^2 = |\mathbf{r}(t) - \gamma \mathbf{a}(\theta)|^2$$

Since approximation error is large when γ is small, the noise \mathbf{n} becomes large.

$$|\gamma| < \sigma$$

When γ is smaller than the standard deviation of noise σ , estimation is not appropriate.

2013/05/15

Wireless Communication Engineering I


54

Experiments in an anechoic chamber

- Measurement

Frequency: 2.484 [GHz]

Distance: about 1.2 [m] (=10 λ)




The fading wave from an ESPAR antenna is measured by a synthetic array with 6 elements.

2013/05/15

Wireless Communication Engineering I

55

Experiments in an anechoic chamber




2013/05/15

Wireless Communication Engineering I

56

- Time property –Received power




Received Signal Power

Estimated DOA

2013/05/15

Wireless Communication Engineering I

57



Cumulative Probability of Received Signal power


Level Crossing Rate of Received Signal Power

2013/05/15

Wireless Communication Engineering I

58

- Spatial property -DOA&AS



Probability Distribution of DOA

Probability Distribution of AS

- The performance of the fading emulator was verified using experimental data.
- Using the ESPAR antenna, evaluation of the array signal processing system becomes a much easier task.

2013/05/15

Wireless Communication Engineering I

59

Conclusion

- Emulation of Rayleigh fading in an anechoic chamber with angular spread is realized.
- It emulates cheaply and simply.
- Estimation by the Maximum Likelihood method is effective.
- It was shown that an ideal angular spread is emulated by M-distribution.

2013/05/15

Wireless Communication Engineering I

60

Future works

- Concurrent emulation of the multiple user
- Control of the phase distribution
- Spatial correlation